CFDEVICE



RUGGEDIZED IN-VEHICLE TABLET

VCM V7 PRO

7" entry-level rugged tablet with CAN bus and wide-voltage input

- **7" 1024×600**
- **Octa-core 1.8 GHz**
- **Android 9.0**
- **4G/LTE (dual SIM opt.)**
- **CAN×2**
- **IP65**
- **9–36V**

KEY FEATURES

- 7" high-brightness display
- Octa-core CPU, GPU supports OpenGL ES 3.1
- IP65 sealing design
- 250K/500K CAN bus (J1939, CANopen, ISO15765)
- 9–36V wide-voltage input with ignition detection
- Compact 0.7 kg body

VCM V7 PRO Specifications

CFDEVICE

System

CPU	Octa-core, 1.8 GHz
GPU	OpenGL ES 3.1
Memory	2GB RAM
Storage	16GB ROM, TF up to 256GB
OS	Android 9.0

Display

Screen	7" 5-point capacitive touch
Resolution	1024×600, 750 cd/m²

Communication

Cellular	4G/LTE (dual SIM optional)
Wi-Fi	2.4/5.8 GHz, 802.11 b/g/n, hotspot
Bluetooth	2.1+EDR / 3.0 / 4.1 LE / 4.2 BLE
GNSS	GPS / BDS / GLONASS; optional cm-level OEM board and inertial navigation

Interfaces

CAN	CAN×2 (J1939, CANopen, ISO15765)
Serial	RS232×2, RS485×1
I/O	12V DC output×2
USB	USB 2.0×1
Ethernet	Ethernet×1 (optional)
Camera	AHD 720p×2

Audio

Audio	Built-in speaker; built-in mic (optional)

Power

Input	9–36V DC
Management	Ignition control

Rugged

Protection	IP65
Vibration / shock	MIL-STD-810
Road vehicle standard	ISO 16750
Operating temperature	-30°C to +70°C
Storage temperature	-40°C to +85°C
Humidity	95%, non-condensing

Mechanical

Dimensions (W×H×D)	194 × 127 × 29 mm
Weight	0.7 kg
Buttons	Power key×1, function keys×2
Connectors	Industrial waterproof connector, SMA×2 (GNSS & 4G)

SOFTWARE ISOBUS VT: Supported · AVM 360°: Contact CF-Device · DMS: Contact CF-Device · MDM: Compatible

APPLICATIONS Precision Agriculture · Construction Machinery · Smart Transportation · Smart Mining · Industrial Control · Warehouse · Bridge Monitoring · Smart Port · Medicine Production